

HIGH PERFORMANCE PENETRATING SEALER

MP90 ECO PLUS

ALL NATURAL STONE, ENGINEERED QUARTZ, POLISHED
PORCELAIN, GROUT



WHAT IT'S FOR

- Seals and protects all natural stone, polished porcelain tile and grout against stains.
- Perfect for all natural stone with polished, brushed and honed finishes.
- Does not alter the material's natural look.
- Excellent protection for kitchen countertops and bathroom vanities.
- Suitable for decorated concrete tile and reconstructed stone.
- Ideal for grout joints, crackle tile, marble resin and stone slabs.

ADVANTAGES

- Makes everyday cleaning easy.
- Eco-friendly: solvent free.
- Is not affected by residual humidity: can be applied 24-48 hours after initial cleaning.
- Does not form a film, discolor or yellow over time.
- FAST SETUP: the surface can be walked on after just 4 hours.
- Certified safe in food preparation areas.
- Very low VOC emissions: contributes towards LEED credits.
- PFOA free: non carcinogenic.

HOW TO USE IT

Matte and honed finish natural stone, decorated concrete tile and manufactured stone: On a clean, dry surface, apply **MP90 ECO PLUS** with a paintbrush or lambswool applicator, making sure to fully saturate the surface. Let sit for 10 minutes and remove any excess with a dry cloth, lambswool pad or sponge.

Polished natural stone, polished porcelain tile: On a clean, dry surface, apply **MP90 ECO PLUS** with a paintbrush or lambswool applicator. Let the product sit for 1 hour then wipe and rub the surface to allow the product to completely penetrate and remove any residue.

Caution: Before full application, test the product on a small, inconspicuous area of the surface or loose sample to check for any discoloration. Apply and leave the product to dry in a well ventilated area. Do not apply the product outdoors if rain is in the forecast.

Note: **MP90 ECO PLUS** does not protect marble, travertine and limestone from acid stains.

Storage temperature: Between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 50°F and 86°F (10°C and 30°C).

FILA. Because It Works.

- **NATURAL LOOK, FAST SETUP: 4 HOURS.**
- **PERFECT FOR KITCHEN AND BATHROOMS COUNTERTOPS.**



Coverage:

1 QT (0.95 L)

Polished porcelain tile ▶ 305-405 sq.ft. (28-38 m²)

Polished natural stone ▶ 205-305 sq.ft. (19-28 m²)

Natural finish stone ▶ 100-205 sq.ft. (9-19 m²)

Coverage rates are indicative and per coat.



Packaging:

1 GAL (3.78 L): 4 plastic bottles per box

1 QT (946 ml) 6 plastic bottles per box

1 PT (473 ml) 12 plastic bottles per box

Distributed by:



Wayne Tile Company

SHOWROOM LOCATIONS

Wayne Showroom

Phone: 973.964.5480
1459 Route 23 South
Wayne, New Jersey 07470

Sussex Showroom

Phone: 973.875.7400
109 State Highway 23
Hamburg, New Jersey 07461

Ramsey Showroom

Phone: 201.825.8000
50 Spring Street
Ramsey, New Jersey 07446

Manasquan Showroom

Phone: 732.359.8418
2418 NJ-35
Manasquan, New Jersey 08736

Rockaway Showroom

Phone: 973.625.3209
333 US-46
Rockaway, New Jersey 07866

Norwood Showroom

Phone: 781.440.0604
151 Carnegie Row
Norwood, Massachusetts 02062

CORPORATE LOCATIONS

Corporate Headquarters

Phone: 973.883.7962
2 Doig Road
Wayne, New Jersey 07470

Commercial Office

Phone: 973.834.8431
100 Alexander Ave
Pompton Plains, New Jersey 07444

For questions and more information, email info@waynetile.com

waynetile.com

